

# Heritage

## Semi-Gloss Polyurethane Wood Finish

Heritage is based on the same superior formulation as our clear polyurethane coating, but with a premium grade flattening agent added to produce a semi-gloss finish which is popular in many residential wood floor finishing applications. For use as a sealer and finish on all interior wood surfaces, Heritage is easy to handle and exhibits superior leveling characteristics. Under normal application conditions, Heritage dries at room temperature in approximately 6 hours to a durable, satin film, which provides excellent resistance to abrasion, wearing, and chemicals. Heritage is Federal VOC emissions law compliant and available in quart containers for sale in areas of the Northeast subject to OTC Commission VOC Regulations and CA subject to CARB regulations.



### APPLICATION & MAINTENANCE

If the composition or origin of an existing finish is unknown, it is strongly recommended that a test patch be applied to determine compatibility and adequate adhesion characteristics. Applying Heritage to floors with a temperature lower than 65° F will result in extended drying and curing times, and should be avoided. **Stir Heritage well before and occasionally during application.**

**FLOOR PREPARATION:** Sanding is advisable for new floors and old, badly worn floors. After sanding, sweep or vacuum the floor to remove wood dust and dirt, and then tack rag the floor using #250 Waterless Cleaner.

**SEALED FLOORS IN GOOD CONDITION:** Clean heavily soiled floors thoroughly with #255 All Prep or #250 Waterless Cleaner. Allow the floor to dry, then screen with an 100-120 grit screen disk. Wet screening using a solution of #255 All Prep diluted 4 ounces per gallon of water, will reduce dusting and clean the floor. Floors may also be dry screened. Dry screening can be more effective at removing deeper scratches and heavy oxidation. Thoroughly sweep or vacuum the floor to remove wood dust and dirt. Tack rag the floor with Waterless Cleaner to remove any fine dirt or dust left from screening.

**APPLYING THE FINISH:** Apply finish only after floor is thoroughly clean and dry. Apply finish with a lamb's wool applicator, brush or weighted drag/t-bar. Pour finish into an applicator pan if applying with a lamb's wool or brush, or a plastic watering can for application with a drag/t-bar. Apply finish in a thin, uniform coat. Generally, one coat is sufficient to provide a positive appearance and performance in recoating procedures. Under warm, low humidity conditions allow a minimum of 5-7 hours between coats. Cold floor temperatures or high humidity can significantly increase drying times. Under warm, low humidity conditions, floors may be opened to light traffic after 24 hours. Adverse drying conditions will extend the amount of time necessary before opening the floor to traffic. Complete curing requires 5-7 days.

**BUFFING BETWEEN COATS:** Screening between coats with a 120 grit or finer screen or surface preparation pad will ensure adhesion and remove application irregularities in the finish providing a smoother final appearance. Sweep or vacuum the floor to remove loose fibers, particles, or dirt. Apply markings, allow to dry and screen. Apply the second coat and buff when dry if desired. Sweep or vacuum carefully, and apply a third coat if required.

### SPECIFICATIONS

Color	1 - 3 / Gardner
Solids	50% minimum
Weight Per Gallon	7.2-7.3
Gloss@60	45-55
Hardness	40 / Sward
Viscosity	A-1 / Gardner
Solvents	Mineral Spirits
Flash Point	105°F minimum
Dry Time	Tack free-5 hours
Water Resistant	24 hours-No effect
Alcohol	1 hour-No effect
Gasoline	24 hours-No effect
Caustic 5%	2 hours-No effect
Soap Resistance	24 hours-No effect
Slip Resistance	(ASTM F-609) 0.5 Minimum
Coverage	400 - 600 Ft. <sup>2</sup> /Gallon
VOC	<450 grams/liter

### SAFETY INFORMATION

Health	1
Flammability	2
Reactivity	0
Personal Protection	B

**Read Safety Data Sheet thoroughly before using.**

**FLAMMABLE** **WARNING: Category 3 Flammable Liquid.** Flash Point - TCC 104° F. Contains Stoddard Solvent CAS #8052-41-3. Keep away from heat and open flame. Irritating to eyes and skin. Do not get in eyes. Minimize contact with skin or clothing. Minimize breathing mists or vapors. Use only with adequate ventilation. Wash after using. Keep container closed when not in use. Do not reuse empty container.

**IRRITANT** **FIRST AID: For eyes:** Flush with water until irritation stops. Seek immediate medical treatment. **For skin:** wash with soap and water. If irritation persists, see a physician. **For ingestion:** Do not induce vomiting. Get immediate medical treatment. **For inhalation:** If overcome or affected, remove victim to fresh air. Get immediate medical attention.



605 Springs Road, Bedford, MA 01730 USA  
Tel: 978.667.5161, Fax: 978.670.5797  
E-mail: [Info@perma.com](mailto:Info@perma.com)  
[www.perma.com](http://www.perma.com)