

Woodcare 101

Solvent Liquid Wax for Wood, Leather, Stone, and Concrete

Designed as a routine maintenance finish for all wood and some composition and stone surfaces, this viscous liquid finish is formulated from select waxes suspended in a solvent-based system. Its lower solids content minimizes build-up, making it ideal for routine maintenance and gloss restoration programs. Easily applied with a low-speed buffing machine and steel wool or polishing pad this one-step application dissolves and suspends black heel marks, oily deposits, and soil, leaving behind a wax finish which can be buffed to a lustrous shine. Used in a routine maintenance program, Wood Care 101 forms a tough film which will prevent damage to expensive wood surfaces from scratching, dirt penetration, and soil or water stains. This premium finish also effectively protects linoleum, terrazzo, marble and ceramic tile surfaces. Wood Care 101 is available in three colors; clear, light oak, or walnut, to allow varying degrees of grain enhancement when used on wood surfaces.



APPLICATION & MAINTENANCE

Wood Care 101 may be used as is from the container, or if a more liquid consistency is desired the can may be placed on a radiator or placed in warm water for several minutes. Sweep or vacuum floor surfaces to remove grit, sand, or dirt. Using the lambswool applicator or a low-speed buffing machine (175-300 Rpm) equipped with a #2 steel wool or spray buffing pad, spread a very thin even coat of wax on the floor. For small areas, or those inaccessible with a buffing machine, the wax can be applied by hand using #2 steel wool, a soft cloth, or lambs wool applicator. The wax will dry to a satin sheen in approximately 15 or 20 minutes. The waxed surface should then be polished with a buffing machine and soft polishing brush, polishing pad, or by hand with a soft cloth or brush to a hard, lustrous shine. Apply additional coats of wax until desired gloss and level of protection is obtained.

SPECIFICATIONS

Solids	8 - 10 %
Solvents	Petroleum distillates, gum turpentine
Flash Point	104° F
Drying Time	15 - 20 minutes
Color	Clear, light oak, dark brown
Weight Per Gallon	6.4 - 6.6
Coverage	2500 ft ² /gallon
Slip Resistance	0.5 minimum
Voc Content	721 grams/liter

SAFETY INFORMATION

Health	1
Flammability	2
Reactivity	0
Personal Protection	B

Read Safety Data Sheet thoroughly before using.

FLAMMABLE **WARNING: Category 3 Flammable Liquid.** Flash point TCC 103°F. Keep away from heat and open flame. Use only with adequate ventilation. Contains Stoddard Solvent CAS# 8052-41-3, and Gum Turpentine CAS# 8006-64-2. **Harmful or Fatal if Swallowed. Irritating to eyes and skin.** Do not get in eyes. Minimize contact with skin or clothing. Wash after using. Do not reuse empty container.



IRRITANT



FIRST AID: If Swallowed, Do Not Induce Vomiting. Contact Physician immediately. In the event of eye contact, call Physician immediately. In case of skin contact, wipe off of effected area. Wash with soap and water. If irritation occurs and persists seek medical treatment.