Traction Clean

Slip Resistant Cleaner/Degreaser

Traction Clean is formulated to provide the cleaning and soil suspension properties necessary to effectively clean and maintain positive slip resistant characteristics in a wide range of settings. These include restaurant and food service areas, restrooms, nursing homes, hospitals, and light industrial manufacturing facilities where food, protein-based soils, light oils, and dirt can cause slippery conditions. Detergents and surfactants effectively break down and suspend soils, removing the potential cause of many slippery floors. Special additives increase the coefficient of friction beyond the level normally inherent in the existing floor surface. Extensive laboratory and field testing on



various types of flooring (including resilient tile, ceramic and stone tile, sealed wood, and concrete) has demonstrated this product's ability to raise the coefficient of friction readings beyond those required by the Occupational Safety and Health Administration, and the 0.6 SCOF recommended by the National Floor Safety Institute, ANSI, and Americans With Disabilities Act.

APPLICATION & MAINTENANCE

Dilute Traction Clean with warm water at the following dilutions, depending on the degree and type of soil to be removed:

Light Duty Cleaning: 6 ounces Traction Clean per gallon of water (1:21).

Medium Duty Cleaning: 8 ounces Traction Clean per gallon of water (1:16).

Heavy Duty Cleaning: 12 ounces Traction Clean per gallon of water (1:10).

Apply with either an autoscrubber or by damp mopping. In order to avoid redepositing grease and protein soils when damp mopping, a two bucket system in which one bucket contains the Traction Clean and one bucket is used for soiled solution, should be used. Heavy deposits of protein soil, dirt, or grease may be addressed by applying Traction Clean at 16 ounces per gallon using a pressurized sprayer, watering can, or mop. Scrub the area with a stiff bristle brush or buffing machine, remove the soiled solution with a wet vacuum or mop, and finish the cleaning procedure by damp mopping. Allow the floor to dry. Do not rinse.

SPECIFICATIONS

| Active Ingredients | Synthetic and Alkaline |
|-----------------------|----------------------------|
| | Detergents, Slip Resistant |
| рН | 11.0-12.0 |
| Free Ammonia | None |
| Free Alkali | None |
| Free Acid | None |
| Phosphates | None |
| Abrasives | None |
| Color | Blue |
| Odor | Moderate |
| Solubility in Water | Complete |
| Freeze/Thaw Stability | 3 cycles |
| Shelf Life | 1 year minimum |
| | at room temp. |
| Flash Point | >200°F |
| Weight Per Gallon | 8.5 lbs |
| Biodegradable | Yes |
| Soil Suspension | Excellent |
| | |

SAFETY INFORMATION

| 2 |
|---|
| 0 |
| 0 |
| В |
| |

Read Safety Data Sheet thoroughly before using.



IRRITANT WARNING: Contains 2-Butoxyethanol CAS# 111-76-2, and 2-Amino Ethanol CAS# 141-43-5, alkaline detergents which may cause irritation in undiluted concentrations. Protective eye glasses and gloves should be worn during use.

FIRST AID: In the event of skin or eye contact, flush thoroughly with clean waterfor 15 minutes. If skin irritation occurs seek medical attention. In the event of eye contact or ingestion seek immediate medical treatment.



605 Springs Road, Bedford, MA 01730 USA Tel: 978.667.5161, Fax: 978.670.5797 E-mail: Info@perma.com www.perma.com