

# Stat-Buff

## Anti-Static Spray Buff/Gloss Maintainer For Stat-Coat Floor Finish

This innovative spray buff is formulated as a companion product for *Stat-Coat*. An integral component of the conductive maintenance program, *Stat-Buff* is designed to extend the static dissipating qualities of *Stat-Coat*, as well as restore the gloss and enhance the appearance of conductive flooring surfaces. Its inherent static dissipating properties make *Stat-Buff* ideal for application in computer rooms, electronic assembly areas, telephone substations, and any other area where positive elimination of static electricity is a prime consideration. Incorporation of *Stat-Buff* into an anti-static flooring maintenance program will extend the period of time between stripping and recoating procedures and result in saving labor and money.



### APPLICATION & MAINTENANCE

**Note: *Stat-Buff 2* is not compatible with *Stat-Buff* or other static dissipative maintenance products.**

Remove loose dirt and soil by sweeping or vacuuming. For best results, the area to be buffed should be damp mopped with *Stat-Clean*. Using a soft or medium pad, spray *Stat-Buff* ahead of the buffing machine, working only small areas at a time.

*Stat-Buff* may also be diluted 32 ounces per gallon of water (1:4) for use as a mop-on restorer. Dilute the *Stat-Buff* in a mop bucket with cold water. Damp mop the area using a lint-free cotton, or combination cotton and synthetic mop. Allow the floor to dry thoroughly, then burnish with a soft pad. Wash and rinse buffing pads after each application.

**For optimum results, do not apply under high humidity conditions.**

### SPECIFICATIONS

|                                      |  |
|--------------------------------------|--|
| Nonvolatile Solids                   | 8 ± 0.5%   |
| Total Active                         | 12%  |
| Resistivity-ASTM D257                | <10 <sup>9</sup> Ohms <sup>2</sup> Max./Cm <sup>2</sup> @<br>40% Relative Humidity |
| pH                                   | 8.0 - 8.8  |
| Gloss 60° - Buffed                   | 85   |
| Color                                | Translucent white  |
| Weight Per Gallon                    | 7.5-8.5  |
| Slip Resistance (ASTM)               | 0.52 minimum   |
| Stability                            | 1 year minimum<br>at room temperature  |
| Freeze/Thaw Stability                | 3 cycles   |
| Drying Time                          | 30 minutes   |
| Water Resistance                     | Good   |
| Gallon Coverage (Feet <sup>2</sup> ) | 2000 - 3500 ft <sup>2</sup>  |
| VOC Content                          | 59 Grams/Liter   |

### SAFETY INFORMATION

|                     |   |
|---------------------|---|
| Health              | 1 |
| Flammability        | 0 |
| Reactivity          | 0 |
| Personal Protection | B |

**Read Safety Data Sheet Thoroughly Before Using.**  
This finish is not a hazardous mixture as defined in 29 CFR 1910. Safety glasses and gloves should be worn during application and handling. **FIRST AID:** In the event of skin or eye contact, flush area with water for 15 minutes. If skin irritation occurs, contact a physician. In the event of eye contact or ingestion, seek immediate medical treatment.



605 Springs Road, Bedford, MA 01730 USA  
Tel: 978.667.5161, Fax: 978.670.5797  
E-mail: [Info@perma.com](mailto:Info@perma.com)  
[www.perma.com](http://www.perma.com)