

Balance

Anti-Slip, Durability and Gloss Enhancing Floor Finish Burnishing Treatment

This revolutionary product increases the durability of vinyl composition tile finishes, while at the same time increasing gloss and slip resistance. Any of Perma's high quality floor finishes that are treated with *Balance* exhibit a truly brilliant gloss which can exhibit a 30-50% increase in finish longevity, as well as having slip resistance characteristics that exceed OSHA, Americans with Disabilities Act (ADA), and National Floor Safety Institute (NFSI) recommendations.



APPLICATION & MAINTENANCE

1. Sweep or dry mop floor to remove any dirt or soil.
2. To obtain optimum results, heavily soiled floors should be cleaned with *Super Blue* or *Geo-Clean* All Purpose Cleaners prior to applying *Balance*.
3. Apply *Balance* (undiluted) in a very thin coat. Using too much *Balance* will make burnishing more difficult and will waste product. One gallon of *Balance* will cover 4000-5000 square feet of flooring.
4. Allow floor to dry.
(Note: Floor may appear hazy at this time)
5. Burnish *Balance* using a 1000 rpm or faster burnishing machine with an aggressive burnishing pad (such as hog's hair) passing over the finish three times for maximum results.

Maintenance of *Balance*

Once the floor has had its initial treatment with *Balance*, floors should be kept clean by washing daily with *Stand Up* or *Aurora*. Burnish the floor with an aqua maintainer pad at least weekly. When your floors don't POP, simply reapply *Balance* to the worn area and burnish.

SPECIFICATIONS

Nonvolatile Solids	Modified Acrylic
Total Active	10%
pH	9.0-9.8
Gloss 60° Buffed	90+
Color	Translucent
Weight Per Gallon	8.31
Slip Resistance (ASTM F-609)	>.6 SCOF
Stability	1 year minimum at room temperature
Freeze/Thaw Stability	3 cycles minimum
Drying Time	15 - 20 minutes
Water Resistance	Excellent
Gallon Coverage (Feet ²)	4000 - 5000
Removability (Gardner)	75 cycles maximum

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Read Safety Data Sheet thoroughly before using.

This product is not a hazardous mixture as defined in 29 CFR 1910.1200. Safety glasses and gloves should be worn during application and handling.

FIRST AID: In the event of skin or eye contact, flush area with water for 15 minutes. If skin irritation occurs seek medical treatment. In the event of eye contact or ingestion, seek immediate medical treatment.



605 Springs Road, Bedford, MA 01730 USA
Tel: 978.667.5161, Fax: 978.670.5797
E-mail: Info@perma.com
www.perma.com