

Aurora

Gloss Enhancing, Slip Resistant Cleaner/Maintainer



Advanced formula technology, utilizing CSAD-0710, has allowed the development of this specially formulated, one-step gloss and slip resistance enhancing cleaner/maintainer. *Aurora* is effective at cleaning and maintaining the gloss of a wide range of floor surfaces, including static dissipative, conductive and standard vinyl tile, synthetic sports flooring, marble, terrazzo, polished stones, and sealed wood. *Aurora* can be applied with either a mop or an automatic scrubber and will not cause a build-up with routine use. Floors maintained with *Aurora* will have slip resistance characteristics that meet or exceed the U.S. Occupational Safety and Health Administration (OSHA), Americans with Disabilities Act (ADA), and National Floor Safety Institutes recommendations for slip resistance.

APPLICATION AND MAINTENANCE

1. Thoroughly sweep the floor to remove any dirt or soil.
2. Floors with heavy concentrations of oil, grease, or animal protein soils should initially be cleaned with a degreaser to obtain optimum results.
3. Dilute *Aurora* between 4 and 8 ounces per gallon with warm water, depending on the soil load and porosity of the floor to be cleaned and treated.
4. *Aurora* may be applied using either a mop and wringer bucket or an automatic scrubber. A two bucket system, in which one bucket holds the solution *Aurora* and one into which the soiled solution is wrung, will provide the most satisfactory results. Damp mop the floor using a clean cotton or cotton/synthetic combination mop. For use in an automatic scrubber, place the *Aurora* solution in the feed tank of the automatic scrubber. The solution may be applied, scrubbed, and vacuumed in one step. Following damp mopping or scrubbing, allow the floor to dry completely, but do not rinse.
5. To restore gloss or repair scuffs, buff the treated area with an appropriate buffing pad, or brush with either a low or high-speed buffing machine.

SPECIFICATIONS

Active Ingredients	Synthetic and Alkaline Detergents, Slip Resistant Additive
Solids	8-10%
pH	8.5 - 9
Slip Resistance (ASTM)	>.6 (SCOF)
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Abrasives	None
Color	Blue
Odor	Moderate
Solubility in Water	Complete
Freeze/Thaw Stability	3 cycles
Shelf Life	1 year minimum
Flash Point	>200°F
Weight Per Gallon	8.5 lbs
Biodegradable	Yes
Soil Suspension	Excellent

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Read Safety Data Sheet thoroughly before using.

This finish is not a hazardous mixture as defined in 29 CFR 1910.1200. Safety glasses and gloves should be worn during application and handling.

FIRST AID: In the event of skin or eye contact, flush area with water for 15 minutes. If skin irritation occurs seek medical treatment. In the event of eye contact or ingestion, seek immediate medical treatment.



605 Springs Road, Bedford, MA 01730 USA
Tel: 978.667.5161, Fax: 978.670.5797
E-mail: Info@perma.com
www.perma.com