

Stat-Gloss

Anti-Static Gloss Restorer/Maintainer For Stat-Coat AIO Floor Sealer/Finish

This innovative high speed burnishing gloss restorer/maintainer is formulated as a companion product for *Stat-Coat AIO*. An integral component of the conductive maintenance program, *Stat-Gloss* is designed to extend the static dissipating qualities of *Stat-Coat AIO*, as well as restore the gloss and enhance the appearance of conductive flooring surfaces.

Its inherent static dissipating properties make *Stat-Gloss* ideal for application in computer rooms, electronic assembly areas, telephone substations, and any other area where positive elimination of static electricity is a prime consideration. Incorporating of *Stat-Gloss* into an anti-static flooring maintenance program will extend the period of time between stripping and recoating procedures and result in saving labor and money.



APPLICATION & MAINTENANCE

Stat-Gloss may be used with the original Stat-Coat formulation as well as Stat-Coat AIO.

Remove loose dirt and soil by sweeping or vacuuming. For best results, the area to be buffed should be pre-cleaned with #137 *Stat-Clean* to remove fine dirt and soils that can become embedded during high speed burnishing procedures. Dilute Stat-Gloss at 8 ounces per gallon of cold water. Using a bucketless mop or comparable system equipped with a microfiber cleaning or finish application flat mop, damp mop the area to be burnished. Allow the mopped area to dry, then, using a 1500-2500 Rpm burnisher equipped with a white or similar soft pad, with limited pressure or burnishing equipment set to "float," burnish areas, making several passes to maintain or restore gloss. NOTE: burnishing area while they are still damp or in high humidity conditions may result in hazing of the finish surface. Wash and rinse buffing pads after each application.

For optimum results, do not apply under high humidity conditions.

SPECIFICATIONS

Active Ingredients	Polymer, Non-Ionic Surfactants, Anti-Static Compounds
Electrostatic Decay Time	0.01 Seconds
pH	6 +/-0.5
Surface Resistivity:	$10^7 - 10^9$ Ohms/M ² per S20.20 2014 @ 100V
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Abrasives	None
Color	Milky
Odor	Mild Detergent
Solubility in Water	100%
Freeze/Thaw Stability	Minimum 3 cycles
Shelf Life	1 year minimum
Flash Point	None
Weight Per Gallon	8.3
Biodegradable	Yes
Soil Suspension	Good
VOC Content	80 grams/liter

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Read Safety Data Sheet thoroughly before using.
Contains Dipropylene Glycol Monomethyl Ether CAS# 34590-94-8. May cause irritation in undiluted concentrations. Safety glasses and gloves should be worn during application and handling. If ingested, drink 1 or 2 glasses of milk or water. Contact a physician immediately. In the event of eye contact, flush area with water for 15 minutes. Consult with a physician. In the event of skin contact, flush the effected area thoroughly with water. If irritation occurs contact a physician.